

## Acrylic Primer, 1 & 5 litre



### DESCRIPTION:

StoneFix acrylic primer is a milky white dispersion of acrylic polymer in a water base, designed to give maximum penetration into the substrate to enhance surface preparation for bonding. Suitable for interior / exterior use and for porous and non porous substrates including; concrete, anhydrite and cement based rendering, ceramic tiles, asphalt and wooden surfaces (inc chipboard, plywood and floor boards).

### FEATURES:

- Internal / External
- Concrete / Screeds
- Chipboard / Timber
- Asphalt / Brickwork
- Plasterboard
- Ceramic Tiles



### CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK  
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk

## SUBSTRATE PREPERATION

Substrates should be hard, sound and free from dust, oil, grease, paint, plaster, or any other contaminants that could provide a barrier to adhesion.

Preparation of the substrate by mechanical means such as scabbling is recognised as the most effective way to provide a good key. Where a substrate has been subject to chemical contamination advice as to any specific precautions must be sought.

## APPLICATION

StoneFix acrylic primer should be mixed with water in proportion from 1:1 (on slightly absorbent surfaces) to 1:3 (on absorbent surfaces) or use undiluted on wooden surfaces. Particularly absorbent surfaces may require a subsequent bonding coat to prevent air rising from the substrate and effecting the final finish. The primer should be applied with a soft brush ensuring that all puddles and any ponding is brushed out prior to screeding. The primer should not be applied to substrates with a temperature of less than +6°C

## COVERAGE

Approximately 10-15m<sup>2</sup> depending on mixing ratio.

## TECHNICAL DATA

Form:	Milky solution.
Specific Gravity:	1.00 – 1.05
pH:	7.00 – 9.00
Flashpoint:	None
Solids Content:	> 50
Application Temp. Range:	+6°C to +30°C
Service temp. Range:	-15°C to +75°C
Durability:	Up to 15 years when used as recommended.
Shelf life:	Up to 15 months when stored in unopened containers. Under cool dry conditions. Avoid frost.
Compatibility:	Can be used in contact with most building and decorating materials but should not be used against bituminous materials.
Limitations:	Should not be used in conditions of continuous immersion, below ground level, in areas of high abrasion (e.g. floor joints).
Colour:	Yellow.

## PACKAGING & STORAGE

StoneFix acrylic primer is supplied in 1 & 5 litre plastic containers and boxed (5 units) 1 litre & (4 units) 5 litre.

Store unopened in a dry place at temperature 5°C, shelf life 15 months from date of manufacture. If the lid is left off the container for a period of time skin will form over the material. The skin should be removed and not mixed into the product.

## HEALTH & SAFETY INSTRUCTIONS

- Aqueous acrylic polymer emulsion, Coalescent, and defoamer.
- Irritating to skin.
- Risk of serious damage to eyes.
- Keep out of reach of children.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
- Wear suitable gloves and eye / face protection.
- If swallowed, seek medical advice immediately and show this container or label.

## QUALITY CONTROL

All StoneFix products are factory blended, tested and packaged to quality control procedure in Accordance with BS EN ISO 9001 series.

## CONTACT DETAILS:

StoneFix, Wetherby Group of Companies, Dalton Industrial Estate, Dalton, North Yorkshire, YO7 3HE. UK  
T: +44 (0)1845 576 514 F: +44 (0)1845 578 777 E: info@stonefix.co.uk W: www.stonefix.co.uk