

# MIKE WYE & Associates

Website ~ [www.mikewye.co.uk](http://www.mikewye.co.uk)

Email ~ [sales@mikewye.co.uk](mailto:sales@mikewye.co.uk)

Telephone 01409-281644

Fax 01409-281669

## PROFESSIONAL GRADE TEX REMOVER

### PROFESSIONAL GRADE TEX REMOVER

Is water-based gel, designed to be applied with a paintbrush or via a Graco type sprayer. Easy to use, it makes light work of removing painted \*Artex.

### VERSATILITY - PROFESSIONAL GRADE TEX REMOVER

Soaks through and softens emulsion and vinyl silk paint and \*Artex type interior textured coatings ready for easy removal.

### SPEED + EFFICIENCY

Faster than	- sanding off
Faster than	- steaming off
Faster than	- re-plastering
Easy to apply	- suitable for large or small areas

### ECONOMY more cost effective than

Manual dry removal  
Hiring a steamer to remove textured coating  
Plastering over

### SAFETY

Non-corrosive  
Non-harmful to handle  
No dangerous vapours

### USER FRIENDLINESS

Safe to use. Non-toxic. Easy to wash tools after use.

### ENVIRONMENTAL FRIENDLINESS

This water-based formulation contains biodegradable, non-caustic, non-corrosive neutral ingredients.

### WHERE TO USE

APL professional grade tex remover is a thick gel with excellent non-drip characteristics. Use it to remove interior Artex\* type coatings and emulsion and/or vinyl silk paint from ceilings and walls.

## **WHAT IT DOES**

APL professional grade tex remover is water based formula which soaks into emulsion paint, vinyl silk paint and Artex\* type textured coatings on interior surfaces, Softening them so that they can be easily scraped away.

## **COVERAGE**

One litre covers from 2 - 4 square metres.  
25 litres covers upto 100 square metres.

## **HOW TO GET THE BEST RESULTS**

1. Protect all areas not to be stripped, including textiles, polished wood surfaces and gloss paint from drips or spillages.
2. Apply professional grade tex remover generously with paintbrush or sprayer. **DO NOT BRUSH OUT.**
3. Where painted allow to soak for 30-40 minutes ( 50 - 60 minutes for ready mixed Artex\*). Check a small area with scraper. **DO NOT ALLOW TO DRY OUT** Reactivate with hot water if drying occurs.

## **NOTE**

Some textured coatings may smell unpleasant when disturbed, but do not generally give off dangerous vapours. Ensure adequate ventilation.

## **CAUTION**

Wear protective goggles when working overhead. Where butyl rubber gloves to remove softened coating. When textured material contains asbestos, relevant regulations apply. Prolonged contact with **PROFESSIONAL GRADE TEX REMOVER** will remove gloss paint.

## **STORAGE**

Keep container securely closed. Store out of sunlight. Protect from frost.

## **DISPOSAL OF WASTE**

Please note that unless you are certain that the coating removed was manufactured after 1985, the waste should be treated as asbestos waste. If paint removed contained lead, then the waste material will contain lead. Dispose in accordance with regulations.

\* Artex is trademark of BPB UK Limited