

Uniclass L623/4:C506	EPIC F212:Y44	Aug 04
CI/SfB	Yq1	(U47)

Health and Safety data sheet



Health & Safety guidelines for the use of:
Hydrated Lime
Natural Hydraulic Lime
Lime Putty

1. Identification of substance

1.1 Product names

Castle Hydrated Lime, Castle Natural Hydraulic Lime and Castle Lime Putty.

1.2 Description

Hydrated lime: An odourless white powder soluble in water. When mixed with cement, sand and water it becomes a binder for building applications (e.g. mortars and renders).

Natural hydraulic lime: An odourless white powder. When mixed with sand and water it becomes a binder for building applications (e.g. mortars and renders).

Lime putty: An aqueous suspension of calcium hydroxide. When mixed with sand it becomes a binder for building applications (e.g. mortars and renders).

2. Supplier/manufacturer

Castle Cement Limited
Park Square
3160 Solihull Parkway
Birmingham Business Park
Birmingham
B37 7YN

Castle Cement Technical Helpline
tel: 0845 722 7853
fax: 01780 727154
e-mail: technical.help@castlecement.co.uk

3. Composition/information on ingredients

3.1 Chemical description

Calcium hydroxide $\text{Ca}(\text{OH})_2$ with some calcium silicates, aluminates, ferro-aluminates and sulfates, small quantities of magnesium and other trace elements.

3.2 Hazardous ingredients

Hazardous ingredient – calcium hydroxide.

4. Hazards identification

- 4.1 Irritating to eyes and skin. Can cause burns in the presence of moisture. It is advisable to ensure that eye wash is available when hydrated lime, natural hydraulic lime or lime putty is handled.

5. First aid measures/ emergency first aid procedures

5.1 Eye contact

Irrigate with water for at least 20 minutes. SEEK MEDICAL ATTENTION. SPEED IS ESSENTIAL.

5.2 Skin contact

Wash affected area immediately with plenty of water. Remove contaminated clothing.

5.3 Ingestion

Do not induce vomiting. Wash mouth with water and drink copious quantities of water. Seek medical advice if necessary.

5.4 Inhalation

Irrigate nose and throat with water for at least 20 minutes. It is advisable to seek medical attention. Remove patient from prolonged and repeated inhalation of high exposure.

5.5 Further medical treatment

No known delayed effects. Prolonged or repeated contact with skin may result in severe irritation or dermatitis. Prolonged or repeated inhalation of high dust concentrations may cause ulceration and perforation of the nasal septum and pneumonitis.

6. Fire-fighting measures

- 6.1 Hydrated lime, natural hydraulic lime and lime putty are not combustible. No special fire-fighting equipment is required. No extinguishing media or explosion hazard is identified.

7. Accidental release measures

7.1 Personal precautions

See 9.3

7.2 Cleaning up

Contain the spillage. Keep the material dry. Act to minimise dust. Avoid contamination of drains or water courses. Spillage into water courses must be alerted to the Environmental Agency. Keep children away from clean up operation.

8. Storage and handling

8.1 General

Keep dust levels to a minimum. Avoid contact with eyes and skin. Use barrier cream if necessary.

8.2 Ventilation requirements

Ventilation equipment should be used in buildings to ensure dust levels are kept below the OEL (see 9.1). All ventilation systems should be filtered before discharge to atmosphere.

8.3 Storage

Minimise contact with air and moisture. Keep separate from flammable materials and chemicals with which it might react. Store in properly designed bunkers or silos. Bagged materials should not be in contact with flammable materials and storage should be in masonry or concrete structures. Bags should be stacked in a safe and stable manner.

8.4 Handling

When handling lime bags, due regard should be paid to the risks outlined in the Manual Handling Operations Regulations. Some bags may have a small amount of lime on the outer surface. Appropriate personal protective clothing (see 9.3) should therefore be used whilst handling.

9. Exposure controls/personal protection

9.1 Occupational Exposure Limit (OEL)

Recommended limit 4mg/m³ (8 hour Time Weighted Average).

9.2 Engineering measures

Handling systems should preferably be enclosed or suitable ventilation installed to maintain atmospheric dust below OEL.

9.3 Personal protective equipment

Long-sleeved overalls, boots and or fabric/composite gloves should be worn, along with wide vision goggles with anti-mist for eye protection. If atmospheric dust exceeds OEL, approved dust respirators or air-streamed helmets should be worn.

10. Physical/chemical properties

10.1 Form

Hydrated lime and natural hydraulic lime – fine dry powder.

Lime putty – an aqueous suspension of calcium hydroxide.

11. Stability and reactivity

Stable.

Avoid exposure to moisture.

Reacts to acids with the evolution of heat.

12. Toxicological information

12.1 Short term effects

- a) Eye contact - can be very painful. May cause partial or total loss of sight if untreated.
- b) Skin contact - irritating to skin. May cause burns in the presence of moisture.
- c) Ingestion - cause corrosion of and damage to gastrointestinal tract.
- d) Inhalation - irritant to respiratory tract.

12.2 Long term effects

May cause irritation to skin and dermatitis. Prolonged and repeated inhalation of high concentrations may damage the respiratory tract.

13. Ecological information

13.1 Mobility

Soluble in water as hydroxide to form alkaline solution. Low mobility in most ground conditions.

13.2 Persistence and degradability

Non biodegradable – reacts with moisture to form calcium hydroxide and reacts with atmospheric carbon dioxide to form calcium carbonate (limestone).

13.3 Bioaccumulative potential

Aquatic toxicity – non toxic LC50 aquatic toxicity values are > 100mg/litre

Colour – white to off-white

Odour – possible earthy odour

pH – 12.4 (as aqueous solution approximately 2g/litre)

Melting (decomposition) point – 580°C

Vapour pressure – 0mmHg at 20°C

Bulk density – 480kg/m³ (loose), 590kg/m³ (compacted)

Solubility in water – 1.76g/litre saturated solution at 100°C

Concentrations have a sterilisation effect in treatment works. Product used in treatment of acid wastes and sewage sludges.

14. Disposal considerations

Hydrated lime, natural hydraulic lime, lime putty and empty packaging can normally be disposed of only at licensed waste facilities. Disposal should be in accordance with local and national legislation. Keep out of reach of children.

15. Transport information

Not classified as hazardous for transport by road and rail.

16. Regulatory information

16.1 The Chemicals (Hazard Information & Packaging) Regulations Statutory Instrument 1746

Classification for supply: Irritant

Classification for conveyance: None

16.2 Risk/safety phrases

Risk phrases

- Risk of serious damage to eyes.
- Contact with wetted Hydrated Lime, wetted Natural Hydraulic Lime or Lime Putty may cause irritation, dermatitis or burns.
- Contact between Hydrated Lime or Natural Hydraulic Lime powder and body fluids (e.g. sweat and eye fluid) may cause skin and respiratory irritation, dermatitis or burns.

Safety phrases

- Avoid eye and skin contact by wearing suitable eye protection, waterproof clothing, waterproof footwear and waterproof gloves.
- Clothing contaminated by wetted Hydrated Lime, wetted Natural Hydraulic Lime or Lime Putty should be removed immediately and washed before re-use.
- Avoid breathing dust.
- Keep out of reach of children.
- On contact with eyes or skin, rinse immediately with plenty of clean water. Seek medical advice after eye contact.

17. Legislation and other information

- Health and Safety at Work etc Act 1974
- Control of Substances Hazardous to Health (Regulations)
- HSE Occupational Exposure Criteria Document Summaries 1993 Edition (ISBN 01 18821202)
- HSE Guidance Note EH26 (Occupational Skin Diseases – Health and Safety Precautions)
- HSE Guidance Note EH40 (Occupational Exposure Limits)
- Any authorised manual on First Aid by St. John's/St. Andrews/Red Cross
- Manual Handling Operations Regulations
- Environmental Protection Act
- Data sheet prepared in accordance with Directive 91/155/ECC

For further information please contact:

Mike Wye & Associates
Buckland Filleigh Sawmills
Buckland Filleigh
Devon EX21 5RN, UK

tel: (+44) 01409 281644

email: sales@mikewye.co.uk

The paper used to produce this leaflet is totally chlorine free and uses pulp from sustainable forests.

L006(Sb)/08/04/pdf