



Brush- and Roll-on Plaster

Product information article no. 165 - 167

09.08.2018

■ General

Brush- and Roll-on Plaster is a lightly filling coat for interior use. Ideal for levelling out slight structural differences on plaster-board and gypsum fibre boards as well as repaired plasters. Gives smooth surfaces a fine plaster texture. Keeps the appearance of fine-grained rubbed plaster, which would inevitably disappear when painted over with smooth wall paints.

■ Uses

Wall and ceiling paint for interior use. Suitable for all structurally-sound, absorbent indoor renders (clay, lime, gypsum and cement), fillers, ingrain wallpaper, pure wallpaper, paper fleece, plasterboard, gypsum fibreboards and concrete.

Also suitable for firmly ingrained, matt and absorbent emulsion paints (please always test on a small sample area first.)

For wet rooms, we recommend Kreidezeit Lime Paint (article no. 888).

■ Properties

- Powder for mixing with water
- Fine plaster texture, grain 0.5 mm
- Ideal substrate for wall glaze techniques
- Levels out slight structural differences on the substrate
- Easy to use, structurable
- Very open to diffusion, antistatic
- Excellent opacity
- Natural white due to fine marble powder
- Without Titanium White
- Wiping resistant and several times overcoatable.
- All ingredients from natural sources
- Free of antidegradants
- Free of synthetic resin binders

■ Composition (Full Declaration)

Marble powder, marble sand, chalk, casein, kaoline, cellulose, soda, methyl cellulose

■ Suitable Tools

Good quality, medium-pile paint roller (polyamide) and paint brush. Airless sprayers (min. air pressure 200 bar).

Recommended from the Kreidezeit range:

Facade brush (article no. P 6080)

Lime brush (article no. P 6082)

Professional roller (article no. 6365)

Professional roller (article no. 6565)

■ Substrate requirements

The substrate must be **absorbent**, structurally sound, clean, dry, solid, non-greasy and free from colouring and permeating ingredients.

■ Preparing the substrate

Thoroughly remove old distemper coats and any other old chalking, loose or unworkable coats. Thoroughly wash any wallpaper adhesive residue off the substrate. Thoroughly sweep sanded surfaces.

Remove binder accumulations and sinter skin from render surfaces. Remove mould oil residue from concrete surfaces. Remove any loose render or wall parts and touch up with a similar material. Penetrating and colouring ingredients in the substrate can be sealed off with Shellac Sealing Primer (article no. 234) before the paint is applied.

Clean any mouldy mineral substrates with soda (article no. 993) or treat with Fungi Stop (article no. 620).

Completely fill any drywall (plasterboard, fibreboard, etc.) (Q4) or cover fully with Paper Fleece (article no. 007).

Fully cover any render substrates with a different structure, different absorbency or any touch-ups using paper fleece, or completely fill with Kreidezeit Wall Filler or Lime Wall Finish to at least 1.5 mm.

■ Primer

Apply a base coat to all renders, fillers, levelled drywall, concrete and old emulsion paints with Vega Primer (article no. 2104) or Casein Primer (article no. 145) and leave to dry completely. Do not apply to paper fleece/wallpaper.

■ Intermediate Coating

For even opacity on high-contrast substrates, it is recommended to apply a diluted Casein Marble Paint in addition to the Casein Primer.

For this, mix 1 kg of Casein Marble Paint in 700 ml clean, cold water without clotting. Leave to soak for 30 minutes and stir again. Application with roller or paint brush. Consumption: approx. 80 - 100 g Casein Marble Paint (powder) per m².

■ Mixing the Plaster

Stir in the specified amount of powder into clean, cold water, until the mixture is smooth. Use a **powerful drill with agitator**. Leave to expand for at least 30 minutes and stir well again before processing.

■ Water required

Mix 1 kg of paint powder with 460 ml of water.

Adjust paint/water mixture to suit the surface; i.e. a little more water may be required for a particular application.



Brush- and Roll-on Plaster

Product information article no. 165 - 167

09.08.2018

■ Application

Application temperature at least 8°C. Stir occasionally during application. Two coats are typically required for full opacity. Do not attempt to cover dark and high-contrast substrates with only one coat of paint; excessive application thicknesses can lead to damage to the coating! Allow previous coats to dry completely before applying another coat. During the application, the wet paint is translucent; it only becomes fully opaque once drying is complete.

Using a paint brush:

Apply evenly with a facade brush in a criss-cross pattern.

Using a roller:

Apply the paint **liberally** and evenly in a criss-cross pattern. Then immediately use a roller in a single direction, without applying any further paint.

The Paint must be applied on the same day as mixing. Do not use paint that smells bad or rotten under any circumstances: Danger of prolonged odour problems even after drying!

■ Tinting

The product can be tinted with up to 10% Kreidezeit earth and mineral pigments (max. 100 g pigment per 1 kg paint powder). Either stir the pigment directly into the preparation water until smooth before mixing in the white Paint powder, or create a paste with a little water and then mix in with the finished Paint. For tinting, please see our Kreidezeit Wall Paints and Renders colour fan. The colour fan is available online at www.kreidezeit.de. Printed versions are available from Kreidezeit and Kreidezeit dealers.

■ Renovation

Brush- and Roll-on Plaster can be coated with Kreidezeit Casein Marble Paint, -Vega Wallpaint, -Lime Paint, -Clay Paint and -Distemper. A previous coat of Vega Primer (article no. 2104) or Casein Primer (article no. 145) makes it easier to paint over.

■ Drying Times at Normal Climate

Safe to coat after approx. 8 hrs.

Thoroughly dried after approx. 24 hrs.

■ Consumption

On even and normal absorbent surfaces approx. 310 g of paint powder per m² per coating.

Accurate consumption values to be determined on site.

■ Package Sizes

Article no. 165 2.5kg

Article no. 166 10kg

Article no. 167 25kg

Please refer to the valid price list for product prices.

■ Storage

If stored cool and dry, the paint powder can be kept for at least 2 years. Tip: Small quantities of mixed paint can be frozen for repair purposes.

■ Cleaning The Tools

Immediately after use with water.

■ Disposing Leftover Product

Do not dispose of leftover product down the drain. Leftover product can easily be composted or disposed of in the household waste when dry. Empty packaging can be recycled.

■ Hazard Classification

None, non-hazardous product.

■ EU VOC Value acc. to 2004/42/EC

VOC limit / Max. VOC content (cat. A/a): 30 g/l (2010),

Product contains max. 1 g/l VOC.

■ Notes

The product is not suitable for correcting major irregularities in the substrate. Casein paints have a typical odour during processing, which disappears over time in a dry environment. Observe possible allergies to natural substances. Keep out of reach of children.

The information above was determined based on our most recent experiences. Due to processing methods and environmental influences, as well as the varying nature of the substrates, liability for the general validity of the individual recommendations is excluded. Users must test the product prior to application to ensure it is fit for the designated purpose (sample coating).

This document is no longer valid if a new version is published or the product is modified. The latest product information is available at Kreidezeit directly or on www.kreidezeit.de