

THECHNICAL DATA SHEET

PRODUCT DESIGNATION:	PRODUCT COMPOSITION / CONSTRUCTION:	
THERMAFLEECE EcoRoll	Sheep's wool based thermal and acoustic insulation for	
	wall, floor and roof applications.	

PROPERTY	METHOD	VALUE
Resistance to Flammability	BS 5803, Pt 4	Pass
Smoulder Resistance	BS 5803, Pt 4	Pass
Ignition Point	Oven Test	560°C
Resistance to Mould	CUAP Veg. Fibre 2002-01-25	Pass
Moth / Beetle Proofing	ISO 3998	Pass
Thermal Conductivity	BS EN 12667	0.039 Wm ⁻¹ K ⁻¹
Recoverability and Thickness	EN 823	Pass
Dimensional Stability	EN 1604	Pass
Short Term Water Absorption	EN 1609 method A	Pass
Water Absorption (@100% RH)	In-house	30% w/w
Specific Heat Capacity	Calculated	1800 Jkg ⁻¹ K ⁻¹
Vapour Resistivity	EN 12086	9 MNsg ⁻¹ m ⁻¹
Embodied Energy (net)	ISO 14040	7 MJkg ⁻¹
Global Warming Potential	ISO 14040	-0.2 kgCO _{2e}
Thickness	Standard spec.	50, 75, 100 & 140mm
Colour	Standard spec.	Mixed grey
Physical Form	Standard spec.	Fibrous batt

STANDARDS & CERTIFICATION

Manufactured in accordance with:

- ISO 9001
- ISO 14001

CONTACT



Buckland Filleigh Sawmills

Devon EX21 5RN Tel: 01409 281644

Email: sales@mikewye.co.uk Web: www.mikewye.co.uk

