

Suppliers of Natural Building and Decorating Products

sales@mikewye.co.uk Telephone: 01409-281644











Lime Plaster – Heritage plaster & Regency grades

Our traditional lime plasters are premixed from selected sands and mature lime putty which are then matured for several weeks. They are typically used internally.

We supply our lime plasters in two formulas and a range of unit sizes.

Our Heritage Plaster mix is suitable for final coat internal plaster skimming (the ratio is 3 sand to 2 mature lime putty by volume).

Our Heritage plaster is a little more lime rich and is suitable for both walls and ceilings and is trowel finished. It can also be used to apply a lime plaster skim to plasterboard, once the board has been suitably prepared with scrim and gypsum board plaster and a special primer called DG27.

Our Regency plaster offers the smoothest of lime plaster finishes and is specifically designed to match the finest historic plasters. Its based upon a 1/1 mix of kiln dried sand with lime putty with added marble flour.

The Lime Putty is made from a refined high calcium quicklime (CaO) that has been slaked and left to mature for a minimum of three months.

Specifications:

Please see below the standards that our raw materials conform to:

Sando-1mm Sand

Lime: BS EN 459-1: 2001

Soundness test (totally slaked) - pass PATS test (moisture content/maturity) - pass 99.99% is finer than 0.18mm particle size

Safety:

Limes are caustic. Always wear eye protection and protective gloves and clothing and follow the safety instructions on the labels.